


Specifications  
Manner  
466177

maharam



001 Magic



002 Carob



003 Porpoise



004 Flint



005 Hush



006 Nuance



008 Cocoa



011 Ember



012 Wagon



013 Ablaze



014 Peel




015 Penny



016 Butterscotch



017 Harvest



020 Parakeet



022 Aquatic



023 Cottage




024 Dahlia




025 Vivid



026 Basin



027 Schooner



028 Slope




029 Silverpoint



030 Lattice




031 Smoky



032 Magnetic



033 Woad



034 Resolute




035 Cruise




036 Atmospheric



037 Cloudburst



038 Tidewater



039 Firth



040 Oceanside



041 Grandeur



042 Comfort



043 Dill



044 Poplar



045 Citronella




046 Passerine




047 Southwest




048 Roseate




049 Charisma



050 Siltstone



051 Kimono



052 Valiant



053 Baroness

# Specifications

Manner

466177

**maharam**

## Application

Seating, Systems, Upholstered Walls

Walls require additional finishes.

Note: This textile is available as a made-to-order pillow.

## Characteristics

Content: 65% Post-Industrial Recycled Polyester, 35% Post-Consumer Recycled Polyester

Finish: Stain Repellent

Additional Finishes Available: Alta, Alta Food and Beverage, Antimicrobial Stain Resistant Finish with Impermeable Backing, Crypton, Flame Resistant Finish, Nanotex

Backing: None

Width: 54" (137cm)

Bolt Size: 45 yards (41 m)

Weight: 16.9 oz/ly (524 gr/lm)

Country of Origin: USA

## Price

Contact your sales representative for pricing.

## Maintenance

W/S-Clean with water-based cleanser or mild, water-free dry cleaning solvent.



## Testing

Abrasion: ASTM D4157, 300,000 double rubs Wyzenbeek

Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

Multiple factors affect fabric durability and appearance retention.

Acoustics: ASTM C423, 0.90 NRC

Flammability: AS/NZS 1530.3

AS/NZS 3837 Unadhered

ASTM E 84 Adhered\*

ASTM E 84 Unadhered

BS 5852 Crib 5\*

CAL 117-2013

CAN ULC S102 Unadhered

EN 1021-1\*

EN 1021-2\*

EN 13501 Unadhered\*

GB/T 17591\*

ISO 5660 Unadhered

NFPA 260

NFPA 701\*

\*passes with additional treatment

Lightfastness: AATCC 16E, 40+ hours



## Specifications

Manner

466177

**maharam**

### **Environmental**

Greenguard and Greenguard Gold Certified

GRS Certified

REACH Compliant

Contains Recycled Content

FR Free

### **Warranty**

3 years: Indoor Seating

3 years: Systems and Upholstered Walls.

© 2013 Maharam

Complete product information at [maharam.com](http://maharam.com)

800.645.3943